APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/938,121	08/23/2001	Yoshiyasu Kubota	SONYJP 3.0-204	1044

530 7590 01/12/2005		EXAMINER
LERNER, DAVID, LITTENBERG, KRUMHOLZ & MENTLIK		YANCHUS III, PAUL B

ART UNIT	PAPER NUMBER
2116	

LERNER, DAVID, LITTENBERG,
KRUMHOLZ & MENTLIK
600 SOUTH AVENUE WEST
WESTFIELD, NJ 07090

DATE MAILED: 01/12/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

-- Th *MAILING DATE* of this communication appears on th cov r she t with the correspond nce addr ss --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE *3* MONTH(S) FROM
THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed
  after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any
  earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on *12 October 2004*.

2a)☐ This action is **FINAL**.   2b)☒ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is
closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) *1-8* is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) *1-8* is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☐ The drawing(s) filed on _____ is/are: a)☐ accepted or b)☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a)☐ All   b)☐ Some * c)☐ None of:

      1.☐ Certified copies of the priority documents have been received.

      2.☐ Certified copies of the priority documents have been received in Application No. _____.

      3.☐ Copies of the certified copies of the priority documents have been received in this National Stage
application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
    Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____ .

5) ☐ Notice of Informal Patent Application (PTO-152)

6) ☐ Other: _____.

DETAILED ACTION

This non-final office action is in response to amendments filed on 10/12/04.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1-8 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nakashima,

US Patent no. 6,085,982[1], in view of, Wong-Insley, US Patent no. 6,131,166.

Regarding claim 1, Nakashima teaches an apparatus [PC Card, 1] adapted for connection to a

host system [personal computer, 3] and for receiving electric power [Vcc from personal

computer, column 5, lines 36-40] from the host system, the apparatus comprising:

a plurality of function blocks [function 1 and function 2], each function block performing

a specified function when selected by the host system [function 1 indicates a modem function

and function 2 indicates an ATA memory function, column 4, lines 43-57]; and

a circuit [function-power-source switching control section, 5] operable to control each

said function block selected by the host system to consume power at an operating rate and to

control each said function block not selected by the host system to consume power at a standby

rate less than said operating rate [column 5, lines 25-44].

---

[1] included in IDS dated 10/27/03

Nakashima teaches that non-selected function blocks are not required to consume power and further teaches disconnecting power to non-selected function blocks to reduce power consumption of a PC Card to a minimum necessary amount. Nakashima does not teach controlling the non-selected function blocks to consume at least some power at a standby rate, which is less than an operating rate. Wong-Insley teaches controlling devices to consume power at levels defined by well known ACPI specification power states. Specifically, Wong-Insley teaches that devices may be placed in the D1 or D2 states instead of the D3 state when power conservation is required. Placing a device in the D1 or D2 state reduces operating power to the device without fully removing power from the device. Consequently, a device in the D1 or D2 state may be returned to a normal operating state, D0, much quicker than a device that in a state, D3, in which no power is consumed [column 14, line 40 – column 15, line 12].

It would have been obvious to one of ordinary skill in the art to combine the teachings of Nakashima and Wong-Insley. Placing the non-selected function blocks in the Nakashima apparatus in a lower power consuming state (ACPI defined D1 or D2 states) instead of a zero power consuming state enables the non-selected function blocks to respond more quickly when they are subsequently selected for normal operation.

Regarding claim 2, Nakashima further teaches

a function code identifying each of said plurality of function blocks [selection-signal, column 5, lines 10-15]; and

a function register [memory, 16] common to said plurality of function blocks, said function register storing said function code for each said function block selected by the host

system, wherein said circuit is operable to control each said function block whose function code

is stored in said function register to consume power at said operating rate and to control each

said function block whose function code is not stored in said function register to consume

power at said standby rate [column 5, lines 25-44 and column 7, lines 30-45].

Regarding claim 3, Nakashima teaches an apparatus [PC Card, 1] adapted for connection

to a host system [personal computer, 3] and for receiving electric power from the host system

[Vcc from personal computer, column 5, lines 36-40], the apparatus comprising:

a plurality of function blocks [function 1 and function 2], each function block performing

a specified function when selected by the host system [function 1 indicates a modem function

and function 2 indicates an ATA memory function, column 4, lines 43-57];

a function code identifying each of said plurality of function blocks [selection-signal,

column 5, lines 10-15];

a circuit [function-power-source switching control section, 5] operable to control each

said function block selected by the host system to consume power at an operating rate and to

control each said function block not selected by the host system to consume power at a standby

rate less than said operating rate [column 5, lines 25-44]; and

a register [memory, 16] common to said plurality of function blocks, said register storing

said function code for each said function block selected by the host system and a power save

value indicating that a power save mode has been selected by the host system [column 5, lines

25-44 and column 7, lines 30-45];

said circuit being operable to control each said function block whose function code is not

stored in said register to consumer power at said standby rate when said power save value is

stored in said register [column 5, lines 25-44].

Nakashima teaches that non-selected function blocks are not required to consume power

and further teaches disconnecting power to non-selected function blocks to reduce power

consumption of a PC Card to a minimum necessary amount. Nakashima does not teach

controlling the non-selected function blocks to consume at least some power at a standby rate,

which is less than an operating rate. Wong-Insley teaches controlling devices to consume power

at levels defined by well known ACPI specification power states. Specifically, Wong-Insley

teaches that devices may be placed in the D1 or D2 states instead of the D3 state when power

conservation is required. Placing a device in the D1 or D2 state reduces operating power to the

device without fully removing power from the device. Consequently, a device in the D1 or D2

state may be returned to a normal operating state, D0, much quicker than a device that in a state,

D3, in which no power is consumed [column 14, line 40 – column 15, line 12].

It would have been obvious to one of ordinary skill in the art to combine the teachings of

Nakashima and Wong-Insley. Placing the non-selected function blocks in the Nakashima

apparatus in a lower power consuming state (ACPI defined D1 or D2 states) instead of a zero

power consuming state enables the non-selected function blocks to respond more quickly when

they are subsequently selected for normal operation.

Regarding claim 4, Nakashima teaches a data processing system, comprising:

an apparatus for performing at least one function [PC Card, 1]; and

a host system [personal computer, 3] for supplying electric power to said apparatus [Vcc

from personal computer, column 5, lines 36-40];

said apparatus including:

a plurality of function blocks [function 1 and function 2], each function block

performing a specified function when selected by the host system [function 1 indicates a

modem function and function 2 indicates an ATA memory function, column 4, lines 43-57];

a function code identifying each of said plurality of function blocks [selection-

signal, column 5, lines 10-15];

a function register[memory, 16] common to said plurality of function blocks, said

function register storing said function code for each said function block selected by the host

system [column 5, lines 25-44 and column 7, lines 30-45]; and

a circuit [function-power-source switching control section, 5] operable to control

each said function block whose function code is stored in said function register to consume

power at an operating rate and to control each said function block whose function code is not

stored in said function register to consume power at a standby rate less than said operating rate

[column 5, lines 25-44]; and

said host system including a writing unit [software, 15] operable to write said

function code for each said function block selected by said host system into said function

register [column 7, lines 30-45].

Nakashima teaches that non-selected function blocks are not required to consume power

and further teaches disconnecting power to non-selected function blocks to reduce power

consumption of a PC Card to a minimum necessary amount. Nakashima does not teach

controlling the non-selected function blocks to consume at least some power at a standby rate, which is less than an operating rate. Wong-Insley teaches controlling devices to consume power at levels defined by well known ACPI specification power states. Specifically, Wong-Insley teaches that devices may be placed in the D1 or D2 states instead of the D3 state when power conservation is required. Placing a device in the D1 or D2 state reduces operating power to the device without fully removing power from the device. Consequently, a device in the D1 or D2 state may be returned to a normal operating state, D0, much quicker than a device that in a state, D3, in which no power is consumed [column 14, line 40 – column 15, line 12].

It would have been obvious to one of ordinary skill in the art to combine the teachings of Nakashima and Wong-Insley. Placing the non-selected function blocks in the Nakashima apparatus in a lower power consuming state (ACPI defined D1 or D2 states) instead of a zero power consuming state enables the non-selected function blocks to respond more quickly when they are subsequently selected for normal operation.

Regarding claim 5, Nakashima teaches a data processing system, comprising:

an apparatus for performing at least one function [PC Card, 1]; and

a host system [personal computer, 3] for supplying electric power to said apparatus [Vcc from personal computer, column 5, lines 36-40];

said apparatus including:

a plurality of function blocks [function 1 and function 2], each function block performing a specified function when selected by the host system [function 1 indicates a modem function and function 2 indicates an ATA memory function, column 4, lines 43-57];

a function code identifying each of said plurality of function blocks [selection-signal, column 5, lines 10-15];

a register [memory, 16] common to said plurality of function blocks, said register storing said function code for each said function block selected by the host system and a power save value indicating that a power save mode has been selected by the host system [column 5, lines 25-44 and column 7, lines 30-45]; and

a circuit [function-power-source switching control section, 5] operable to control each said function block whose function code is stored in said function register to consume power at an operating rate and to control each said function block whose function code is not stored in said function register to consume power at a standby rate less than said operating rate [column 5, lines 25-44].

Nakashima teaches that non-selected function blocks are not required to consume power and further teaches disconnecting power to non-selected function blocks to reduce power consumption of a PC Card to a minimum necessary amount. Nakashima does not teach controlling the non-selected function blocks to consume at least some power at a standby rate, which is less than an operating rate. Wong-Insley teaches controlling devices to consume power at levels defined by well known ACPI specification power states. Specifically, Wong-Insley teaches that devices may be placed in the D1 or D2 states instead of the D3 state when power conservation is required. Placing a device in the D1 or D2 state reduces operating power to the device without fully removing power from the device. Consequently, a device in the D1 or D2 state may be returned to a normal operating state, D0, much quicker than a device that in a state, D3, in which no power is consumed [column 14, line 40 – column 15, line 12].

It would have been obvious to one of ordinary skill in the art to combine the teachings of

Nakashima and Wong-Insley. Placing the non-selected function blocks in the Nakashima

apparatus in a lower power consuming state (ACPI defined D1 or D2 states) instead of a zero

power consuming state enables the non-selected function blocks to respond more quickly when

they are subsequently selected for normal operation.

Regarding claim 6, Nakashima teaches that the host system includes a writing unit

[software, 15] operable to write said function code for each said function block selected by said

host system and said power save value into said register [column 7, lines 30-45].

Regarding claim 7, Nakashima teaches a data processing system including a host system

[personal computer, 3] and an apparatus [PC Card, 1] for performing functions, the apparatus

including a plurality of function blocks [function 1 and function 2] and a register [memory, 16]

common to the plurality of function blocks, each function block performing a specified function

when selected by the host system [function 1 indicates a modem function and function 2

indicates an ATA memory function, column 4, lines 43-57], and a method of controlling power

consumption of the apparatus, comprising:

supplying electric power from the host system to each of the plurality of function blocks

at a standby rate of consumption [Vcc from personal computer, column 5, lines 36-40];

operating the host system to select a function block from among the plurality of function

blocks [column 5, lines 1-25 and column 7, lines 30-45];

controlling the host system to send the function code [selection-signal] of the selected

function block to the apparatus [column 5, lines 1-25 and column 7, lines 30-45];

controlling the apparatus to set the function code of the selected function block to the

register [memory, column 7, lines 30-45]; and

reading the function code of the selected function block from the register and controlling

power consumption of the plurality of function blocks so that the selected function block

consumes power at an operating rate of consumption greater than said standby rate of

consumption and each said function block whose function code is not stored in the register

consumes power at said standby rate of consumption [column 5, lines 25-44].

Nakashima teaches that non-selected function blocks are not required to consume power

and further teaches disconnecting power to non-selected function blocks to reduce power

consumption of a PC Card to a minimum necessary amount. Nakashima does not teach

controlling the non-selected function blocks to consume at least some power at a standby rate,

which is less than an operating rate. Wong-Insley teaches controlling devices to consume power

at levels defined by well known ACPI specification power states. Specifically, Wong-Insley

teaches that devices may be placed in the D1 or D2 states instead of the D3 state when power

conservation is required. Placing a device in the D1 or D2 state reduces operating power to the

device without fully removing power from the device. Consequently, a device in the D1 or D2

state may be returned to a normal operating state, D0, much quicker than a device that in a state,

D3, in which no power is consumed [column 14, line 40 – column 15, line 12].

It would have been obvious to one of ordinary skill in the art to combine the teachings of

Nakashima and Wong-Insley. Placing the non-selected function blocks in the Nakashima

apparatus in a lower power consuming state (ACPI defined D1 or D2 states) instead of a zero

power consuming state enables the non-selected function blocks to respond more quickly when they are subsequently selected for normal operation.

Regarding claim 8, Nakashima teaches a data processing system including a host system [personal computer, 3] and an apparatus [PC Card, 1] for performing functions, the apparatus including a plurality of function blocks [function 1 and function 2], each function block performing a specified function when selected by the host system [function 1 indicates a modem function and function 2 indicates an ATA memory function, column 4, lines 43-57], and a method of controlling power consumption of the apparatus, comprising:

supplying electric power from the host system to each of the plurality of function blocks at a standby rate of consumption [Vcc from personal computer, column 5, lines 36-40];

operating the host system to select a function block from among the plurality of function blocks [column 5, lines 1-25 and column 7, lines 30-45];

controlling the host system to send a notification [selection-signal] to the apparatus identifying the selected function block [column 5, lines 1-25 and column 7, lines 30-45];

controlling power consumption of the plurality of function blocks so that each function block not selected by the host system consumes power at the standby rate of consumption and the selected function block consumes power at an operating rate of consumption greater than the standby rate of consumption [column 5, lines 25-44].

Nakashima teaches that non-selected function blocks are not required to consume power and further teaches disconnecting power to non-selected function blocks to reduce power . consumption of a PC Card to a minimum necessary amount. Nakashima does not teach controlling the non-selected function blocks to consume at least some power at a standby rate,

which is less than an operating rate. Wong-Insley teaches controlling devices to consume power

at levels defined by well known ACPI specification power states. Specifically, Wong-Insley

teaches that devices may be placed in the D1 or D2 states instead of the D3 state when power

conservation is required. Placing a device in the D1 or D2 state reduces operating power to the

device without fully removing power from the device. Consequently, a device in the D1 or D2

state may be returned to a normal operating state, D0, much quicker than a device that in a state,

D3, in which no power is consumed [column 14, line 40 – column 15, line 12].

It would have been obvious to one of ordinary skill in the art to combine the teachings of

Nakashima and Wong-Insley. Placing the non-selected function blocks in the Nakashima

apparatus in a lower power consuming state (ACPI defined D1 or D2 states) instead of a zero

power consuming state enables the non-selected function blocks to respond more quickly when

they are subsequently selected for normal operation.

Response to Arguments

Applicant's arguments with respect to claims 1-8 have been considered but are moot in

view of the new ground(s) of rejection.

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Paul B Yanchus whose telephone number is (571) 272-3678. The

examiner can normally be reached on Mon-Thurs 8:00-6:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Lynne H Browne can be reached on (571) 272-3670. The fax phone number for the

organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Paul Yanchus
January 6, 2005

LYNNE H. BROWNE
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2100